

# COMPANY PROFILE

2026

Solanki Global Venture is a merchant exporter from Vapi, supplying export-grade paper and sourcing packaging paper from India (Gujarat) to global markets, The global supply chain demands Reliable Partners in India.

# ABOUT COMPANY

## Who We Are & What We Do

We operate as a **merchant exporter** specialists in the sourcing and supply of **paper and paper-based packaging products** from India. Working closely with **established manufacturing partners**, we connect reliable production capabilities with the requirements of international buyers.

## Our Sourcing & Quality Approach

Our approach is built around **clearly defined** specifications, consistent sourcing, and structured coordination from inquiry to shipment. By aligning product parameters such as **GSM, BF, size**, and **grade** with buyer needs, we ensure that each supply meets the intended application and **international usage standards**.

## Our Services & Commitment to Buyers

Beyond product supply, we support buyers through **end-to-end export coordination**, including **supplier selection**, order execution, and shipment support. With a focus on professionalism, transparency, and **long-term partnerships**, we aim to deliver dependable quality and reliable service to global packaging and industrial buyers.

# VISION

To be a **trusted sourcing** and **export partner** for paper and paper-based packaging products, connecting **reliable Indian manufacturing** capabilities with global buyer requirements through **consistency, transparency, and professional execution.**

# MISSION

01

To source and supply **quality, export-grade paper products** aligned with **international buyer specifications**

02

To work with **established manufacturing** partners to ensure **consistency** and **reliability** in every supply

03

To maintain a **structured sourcing approach** that supports **quality alignment** and **application suitability**

04

To support **global buyers** through **dependable execution** and **long-term partnerships**

# PRODUCT LIST

SR. NO.	PRODUCT NAME	HS CODE (6-digit)
1	<b>Kraft Paper</b>	<b>4804.29</b>
2	<b>Test-liner Paper</b>	<b>4805.24</b>
3	<b>Fluting Medium</b>	<b>4805.12</b>
4	<b>Kraft Liner</b>	<b>4804.19</b>
5	<b>Paper Cups</b>	<b>4823.69</b>
6	<b>Paper Bags (Shopping / Food bags)</b>	<b>4819.4</b>
7	<b>Recycled Paper / Waste-based Paper</b>	<b>4805.92</b>

# Kraft Paper

## Product Overview

Kraft Paper is a strong, durable paper produced mainly from virgin wood pulp using the kraft process. It is known for its high tear resistance and strength.

## Technical Specification

Parameter	Specification
<b>GSM Range</b>	<b>50 – 350 g/m<sup>2</sup></b>
<b>GSM Tolerance</b>	<b>±5%</b>
<b>Burst Factor (BF)</b>	<b>12 – 30</b>
<b>Tensile Strength (MD)</b>	<b>3.0 – 6.5 kN/m</b>
<b>Tensile Strength (CD)</b>	<b>1.5 – 3.5 kN/m</b>
<b>Moisture Content</b>	<b>6 – 8%</b>
<b>Finish</b>	<b>MG / MF</b>
<b>Shade</b>	<b>Natural Brown</b>
<b>Raw Material</b>	<b>Virgin / Recycled Pulp</b>
<b>Form</b>	<b>Roll / Sheet</b>

## Standard Reel Details

- Width: 500 mm – 2800 mm
- Diameter: Up to 1200 mm
- Core ID: 76 mm (3 inch)

## Applications

- Wrapping, packaging, paper bags, industrial packing.

- Technical specifications are indicative and may vary depending on GSM, raw material, and production batch. Final specifications will be confirmed at the time of order.

# Test liner Paper

## Product Overview

Test Liner Paper is a recycled-based linerboard used as the outer or inner layer of corrugated boards.

## Technical Specification

Parameter	Specification
<b>GSM Range</b>	<b>110 – 350 g/m<sup>2</sup></b>
<b>GSM Tolerance</b>	<b>±5%</b>
<b>Burst Factor (BF)</b>	<b>18 – 35</b>
<b>Ring Crush Test (RCT)</b>	<b>3.0 – 6.5 kN/m</b>
<b>Cobb (Water Absorption)</b>	<b>≤ 100 g/m<sup>2</sup></b>
<b>Moisture Content</b>	<b>6 – 8%</b>
<b>Finish</b>	<b>(MF)Machine finished</b>
<b>Shade</b>	<b>Natural Brown</b>
<b>Raw Material</b>	<b>Recycled Pulp</b>
<b>Form</b>	<b>Roll / Sheet</b>

## Standard Reel Details

- Width: 500 mm – 2800 mm
- Diameter: Up to 1200 mm
- Core ID: 76 mm (3 inch)

- Technical specifications are indicative and may vary depending on GSM, raw material, and production batch. Final specifications will be confirmed at the time of order.

## Application

- Inner & outer liners of corrugated boxes.

# Fluting Medium

## Product Overview

Fluting Medium is a specialized paper grade used as the corrugated (wave-shaped) inner layer in corrugated board production. It plays a critical role in providing strength, rigidity, and cushioning to corrugated packaging.

## Technical Specification

Parameter	Specification
<b>GSM Range</b>	<b>90 – 220 g/m<sup>2</sup></b>
<b>GSM Tolerance</b>	<b>±5%</b>
<b>Burst Factor (BF)</b>	<b>12 – 22</b>
<b>Ring Crush Test (RCT)</b>	<b>4 – 7 kN/m</b>
<b>Concord Medium Test (CMT)</b>	<b>60 – 110 N</b>
<b>Moisture Content</b>	<b>6 – 8%</b>
<b>Finish</b>	<b>Machine finished</b>
<b>Shade</b>	<b>Brown</b>
<b>Raw Material</b>	<b>Recycled Pulp</b>
<b>Form</b>	<b>Reel / Sheet</b>

## Standard Reel Details

- Width: 500 mm – 2800 mm
- Diameter: Up to 1200 mm
- Core ID: 76 mm (3 inch)

## Application

- Middle fluting layer in corrugated boxes.

- Technical specifications are indicative and may vary depending on GSM, raw material, and production batch. Final specifications will be confirmed at the time of order.

# Kraft Liner

## Product Overview

Kraft Liner is a premium linerboard made from virgin or mixed pulp, used as the outer layer of corrugated packaging.

## Technical Specification

Parameter	Specification
<b>GSM Range</b>	<b>120 – 250 GSM</b>
<b>GSM Tolerance</b>	<b>±5%</b>
<b>Burst Factor (BF)</b>	<b>28 – 40</b>
<b>Ring Crush Test (RCT)</b>	<b>5.0 – 8.0 kN/m</b>
<b>Cobb (Water Absorption)</b>	<b>≤ 80 g/m<sup>2</sup></b>
<b>Moisture Content</b>	<b>6 – 8%</b>
<b>Finish</b>	<b>Machine finished</b>
<b>Shade</b>	<b>Brown</b>
<b>Raw Material</b>	<b>Virgin / Recycled Pulp</b>
<b>Form</b>	<b>Reel / Sheet</b>

## Standard Reel Details

- Width: 500 mm – 2800 mm
- Diameter: Up to 1200 mm
- Core ID: 76 mm (3 inch)

- Technical specifications are indicative and may vary depending on GSM, raw material, and production batch. Final specifications will be confirmed at the time of order.

## Application

- Corrugated Boxes
- Heavy-Duty, Printed and industrial Packaging
- Branded Packaging

# Paper Cups

## Product Overview

Paper Cups are disposable containers manufactured from food-grade paperboard, typically coated for liquid resistance.

## Technical Specification

Parameter	Specification
<b>Sizes</b>	<b>4 oz – 16 oz</b>
<b>Material</b>	<b>Food-grade paperboard</b>
<b>Coating</b>	<b>PE / PLA</b>
<b>Wall Type</b>	<b>Single wall / Double wall</b>
<b>Printing</b>	<b>Flexo / Offset</b>
<b>Color</b>	<b>White / Printed</b>
<b>Leak Proof</b>	<b>Yes</b>
<b>Usage Temperature</b>	<b>Hot &amp; Cold beverages</b>

## Packaging Format

- Sleeves (Typically 50 Pcs Per Sleeve)
- Export cartons
- Palletized shipment

- Technical specifications are indicative and may vary depending on GSM, raw material, and production batch. Final specifications will be confirmed at the time of order.

# Printed Paper Bags

## Product Overview

Printed Paper Bags combine functionality with branding, offering a sustainable alternative to plastic bags.

## Technical Specification

Parameter	Specification
<b>Sizes</b>	<b>Customize per required</b>
<b>Material</b>	<b>Kraft Paper</b>
<b>GSM Range</b>	<b>80 – 150 GSM</b>
<b>GSM Tolerance</b>	<b>±5%</b>
<b>Bag Type</b>	<b>Flat / SOS / Square Bottom</b>
<b>Handle Type</b>	<b>Flat / Twisted</b>
<b>Printing</b>	<b>Flexo / Offset</b>
<b>Color</b>	<b>Brown / White / Printed</b>
<b>Finish</b>	<b>Natural / Printed</b>

## Material Options

- Brown Kraft Paper
- White Kraft Paper
- Recycled Kraft Paper

- Technical specifications are indicative and may vary depending on GSM, raw material, and production batch. Final specifications will be confirmed at the time of order.

# Recycled Paper

## Product Overview

Recycled Paper is manufactured using post-consumer or post-industrial waste paper, supporting sustainability and cost efficiency.

## Technical Specification

Parameter	Specification
<b>GSM Range</b>	<b>80 – 250 GSM</b>
<b>GSM Tolerance</b>	<b>±5%</b>
<b>Burst Factor (BF)</b>	<b>10 – 18</b>
<b>Ring Crush Test (RCT)</b>	<b>As per GSM</b>
<b>Moisture Content</b>	<b>6 – 9%</b>
<b>Finish</b>	<b>Machine finished</b>
<b>Shade</b>	<b>Natural Brown / Grey</b>
<b>Raw Material</b>	<b>100% Recycled Fiber</b>
<b>Form</b>	<b>Reel / Sheet</b>

## Standard Reel Details

- Width: 500 mm – 2800 mm
- Diameter: Up to 1200 mm
- Core ID: 76 mm (3 inch)

- Technical specifications are indicative and may vary depending on GSM, raw material, and production batch. Final specifications will be confirmed at the time of order.

# VALUE ADDED SERVICE

- **Specification Alignment**

Clear definition of GSM, BF, size, grade, and application requirements to match buyer expectations.

- **Multi-Source Coordination**

Access to multiple established manufacturing partners to support consistency and supply flexibility.

- **Shipment Readiness Support**

Coordination of packing, scheduling, and shipment preparation for smooth export execution.

- **Single-Point Communication**

Centralized coordination to ensure clear, timely communication throughout the order process.

# CONTACT US

## We are ready to assist you

For product inquiries, specifications, or export-related discussions, please contact our team. We support international buyers with timely responses and structured communication for paper and packaging product sourcing.



Sai Veer Industrial Park, No-25, Karvad,  
Vapi, Gujarat-396193



+91-9724355019



[www.solankiglobalventure.com](http://www.solankiglobalventure.com)



[Info@solankiglobalventure.com](mailto:Info@solankiglobalventure.com)